

TIXOTROPIC EPOXY GLUE

CHARACTERISTICS

Is a bi-component epoxy glue, the two parts are automatically pre-dosed thanks to the cartridge in which it is packaged. Suitable for gluing marble, stone, granite, quartz and ceramics in a safe and lasting way.

The dosage between the two parts is regulated by a mixing spout and the special gun which makes the mixing between the two components safe and precise in line with the exact application ratio of the compound. Suitable for external and internal use with very low yellowing, it is available in a neutral version and in a colored version. Approved for food contact.



FEATURES

tixotropic



COLOUR

transparent



TYPE

gel



CONTAINER

ADR



APPLICATION

All the surfaces involved must be cleaned and free of dust and grease. In case of glossy and/or smooth surfaces it is advisable to treat them with sandpaper before gluing and clean again. Remove the threaded extremity and uncap the cartridge. Fix the mixer to the cartridge through the threaded nozzle. Before applying the glue to the surfaces let spurge around 5 grams. After usage, clean the nozzle, replace the cap and discard the mixer after use. SILVER BOND Cartridge is used to glue natural stones, engineered stone, quartz and ceramics.


APPLICATION MATERIAL




Granite




Ceramic



Natural stone



Quarz



Marble

APPLICATION TOOLS



gun

WHERE TO APPLY ?



indoor or outdoor

FAQ:

FORMAT	SHELF LIFE
250 ml	1 year

This sheet cannot be reproduced or changed in any of its parts without permission of Global Shipping S.p.a.Unipersonale.

